

TOSHIBA

INDUSTRIAL

BX410T series

- High-performance 4" thermal label printers
- Flexible device integration
- Reliable hardware with long-life printheads
- Includes ribbon-saving technology
- Supports IoT device management
- RFID-ready



The next-generation of industrial printing.


Superior hardware meets smart, cloud-based technology.

In today's fast-paced industrial environment, maintaining peak performance under heavy workloads can be challenging. The BX410T series ensures exceptional reliability and efficiency to keep your operations running smoothly, even in the most demanding conditions.

Powered by Toshiba's innovative A-BRID Operating System and a high-performance dual-core CPU, this printer provides smart, cloud-based connectivity for seamless integration and remote management. By combining trusted hardware with advanced technology, the BX410T series helps streamline workflows, reduce downtime, and enhance productivity—offering a future-proof solution that grows with your business.



Industrial
Printing



Toshiba's A-BRID
Operating System



Superior User
Experience



Integrated
RFID



Seamless
Connectivity

Bridging tradition and innovation.

- The BX410T series combines field-proven hardware with a dual-core CPU running both a real-time operating system and a Linux OS, creating Toshiba's A-BRID ecosystem.
- Toshiba's A-BRID Operating System integrates multifunction printer technology into label printers, enabling advanced IT applications.

Stay ahead with unmatched productivity.

- Renowned hardware reliability with long-life printheads minimize downtime and deliver unmatched total cost of ownership (TCO).
- Toshiba's ribbon-save technology and long-length ribbons maximize operating time with minimal user intervention.

Superior user experience.

- New features like the integrated label near-end detection and a full-color display streamline daily operations.
- QR code-based user functions link mobile devices to the printer or connect to support resources like help desks.

Integrated RFID analyzer & direct encoding.

- Toshiba's A-BRID system architecture supports advanced applications, such as the Toshiba RFID analyzer, running directly on the printer.

Turn your printer into a labeling hub.

- Embedded apps transform printers into standalone print stations, enabling data directly from barcode scanners or keyboards without the need for a workstation.
- Security is paramount: Only Toshiba-tested and certified whitelisted apps are allowed to run on A-BRID.

Take control of your fleet—from anywhere.

- Toshiba's proprietary cloud service infrastructure Elevate Sky® MFPCoconnect automatically manages counters, logs, and firmware updates.
- Centrally monitor, manage and support your printer fleet remotely with SOTI Connect.

Integration made easy.

- Native PDF printing and automatic legacy language selection simplify setup.
- Printer cloning replicates configurations seamlessly across devices.

Seamless connectivity.

- Standard USB and LAN ports, plus an optional Wi-Fi module, provide versatile connection options to suit your needs.



The reliable BX410T series is an ideal printing solution for demanding environments, such as:

- Transportation
- Warehouses
- Manufacturing
- Retail



Unlock next-level connectivity, customization, and integration with Toshiba's A-BRID technology.

Built for next-generation printers, Toshiba's A-BRID Operating System revolutionizes industrial printing by delivering unmatched connectivity, seamless customization, and effortless integration.

Real-time PDF Printing: Automatic rotation & scaling for faster document handling.

Effortless Integration: Streamlined data conversion for easy system compatibility.

Automatic Language Detection: Eliminates manual configuration with auto-emulation for simplified setup.

Remote Management: Monitor & manage your printer fleet with Elevate Sky® MFPCoconnect & SOTI Connect.

Simplified Deployment: Quick setup with printer cloning & intuitive web interface.

Standalone Printing: Direct printing from mobile devices or barcode scanners for added convenience & flexibility.

Advanced Security: Robust protection for all networked devices & data.



BX410T series

Model		Media	
BX410T-GS02		Alignment	Center
Resolution	203 dpi (8 dots/mm)	Backing Paper Width	30–107 mm
BX410T-TS02		Label Thickness	Label: 0.13–0.17 mm Tag: 0.08–0.25 mm
Resolution	305 dpi (11.8 dots/mm)	Inner Media Core Diameter	76.2 mm
General		Outer Media Roll Diameter	Max. 200 mm
Printhead	Near Edge	Media Type	Vellum Paper and Labels, Matte Coated Paper, Glossy Coated Paper, Synthetic Film, PET Film, Polyimide
Print method	Direct Thermal/Thermal Transfer	Media Formats	Roll, Fanfold
Dimensions (W x D x H)	278x 460 x 310 mm	Near End Detection	Adjustable, e.g. 10% Remaining
Weight	17kg	A-BRID Operating System	
User Interface	Full Color LCD, 2x LED, 11 x Key	CPU	Dual Core, 1.0 GHz
Operation Temperature/Humidity	5°C–40°C/25–85% Non-Condensing Relative Humidity (RH)	A-BRID Dual OS	System: Linux-based Print Engine: RTOS
Storage Temperature/Humidity	-40°–40°C/10–90% Non-Condensing Relative Humidity (RH)	Memory	1 GB RAM, 8 GB ROM
Power Supply	AC 100-240V, 50/60 Hz	Expansion Memory	Via USB Drive
Print		Embedded Applications	SDK for Custom Applications, e.g. for Standalone Printing
Sensor	Reflective, Transmissive	Print Data Converter	Automatically Convert or Correct Incoming Data
Max. Print Speed	356 mm/Second (14ips)	PDF Printing	Auto Print of PDFs, Auto Rotate, Auto Scaling
Max. Print Width	104 mm	Software & Connectivity	
Print Length		Emulation	Auto-detection of TPCL, ZPL II, DPL, SBPL, PDF
Batch	6–1,496 mm	Printer Driver	Windows 11/10, Windows Server 2022/2019, SAP, CUPS Driver for Linux, macOS
Cut	21.4–1,496 mm	SDK	iOS, Android, Windows, Java 200 Pages Per Document
Peel-off	21.4–1,496 mm	Interface	USB 2.0 HS (USB host/HID support), LAN 10/100/1000 BaseT, RS232*, WLAN 802.11ac/a/b/g/n/ax*, Expansion I/O(1)
Barcodes	EAN8, EAN13, JAN8, JAN13, UPC-A, UPC-E, NW7, CODE 39, Code 93, ITF, MSI, Code 128, EAN 128, Industrial 2 of 5, POSTNET, RM4SCC, KIX-code, GS1 DataBar, USPS Intelligent Mail, Customer Barcode	Language Mode	TPCL
2D Codes	Data Matrix, PDF417, MaxiCode, QR Code, Micro QR Code, Micro PDF417, CP Code, AZTEC Code, GS1 QR Code, GS1 Data Matrix	Label Software	NiceLabel Free, BarTender UltraLite
Fonts	Bitmap Font, Outline Font, Price Font, Optional TTF, OTF, Writable Characters	IoT Device Management	SOTI Connect, Elevate Sky® MFPConnect
Ribbon		Options	
Ribbon Width	Max. 112 mm	Disc Cutter, Rotary Cutter, Peel-off Module, Ribbon Save Module, External Media Guide, RS232, Wireless LAN, EX I/O, UHF RFID Kit, HF RFID Kit, Real Time Clock	
Ribbon Core Size	25 mm(±0.2 mm)	*Optional	
Max. Ribbon Length	600 m, 800 m		
Max. Ribbon Diameter	90 mm		
Near End Detection	30 or 70 m Selectable		
RFID			
RFID Module	Optional UHF (EPC Gen2) Optional HF (ISO 15693, ISO14443 Type A)		
RFID Analyzer	Integrated RFID Analyzer		



business.toshiba.com

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation.

Corporate Office	25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000
East Coast	959 Route 46 East, 5th Floor, Parsippany, NJ 07054 Tel: 973-316-2700
Midwest	8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Tel: 773-380-6000
South	2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385
West Coast	25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000
Website	business.toshiba.com